


EPM63-50 Vented PMDC motor

PARVALUX

Ø90 mm frame // 50 mm stack



Part number key

Modular	#####
Standard	#####
Special	#####

Available on request: Custom shaft length and diameter, shaft on both sides, special windings for specific voltages and speed, higher IP protection class, custom flanges and connectors

All products are built in accordance to performance tolerances from EN60034-1:2010. As continuous improvement, Parvalux periodically test their product range to ensure test results are as accurate as possible and are therefore subject to change. Please ensure you are using the latest datasheets found on our website

Technical data

1 Part number		V6350-3K12	V6350-3K12	V6350-3K12	V6350-3K12
2 Nominal power	W	327	327	327	327
3 Nominal voltage	V	12	24	40	48
4 No load speed	rpm	4548	3992	3881	3854
5 No load current	A	5.50	2.60	1.50	1.04
6 Nominal speed	rpm	3000	3000	3000	3000
7 Nominal continuous torque (S1)	Nm	1.0	1.0	1.0	1.0
8 Nominal continuous current (S1)	A	46.0	20.0	11.4	7.0
9 Max. intermittent torque (S3)	Nm	1.6	1.6	1.6	1.6
10 Stall current	A	156.0	83.0	47.0	38.7
11 Stall torque	Nm	3.8	4.8	4.7	4.6
12 Stack length	mm	50	50	50	50
13 Maximum efficiency	%	69	70	70	70
14 Terminal resistance - phase to phase	Ω	0.08	0.29	0.85	1.24
15 Terminal inductance - phase to phase	mH	-	-	-	-
16 Speed constant	rpm/V	371	159	93	77
17 Torque constant	Nm/A	0.025	0.059	0.100	0.123
18 Speed torque gradient	rpm/Nm	1200	831	831	831
19 Rotor inertia	gcm ²	6130	6130	6130	6130

Thermal data

20 Ambient temperature	°C	40
------------------------	----	----

Mechanical data

21 Radial load [distance from flange]	N [mm]	200 [15]
---------------------------------------	--------	----------

Other data

22 Number of poles		4
23 Weight	Kg	3.1
24 IP rating		IP21
25 Enclosure		Ventilated
26 Insulation Class		F
27 Reversible		Yes

Modular system

