


# ESCON Data



	ESCON Module 50/8	ESCON Module 50/8 HE
DC motors up to (continuous / maximum)	400 W / 750 W	400 W / 750 W
EC motors up to (continuous / maximum)	400 W / 750 W	400 W / 750 W
<b>Sensors</b>		
	Digital Incremental Encoder (2 channel with or without Line Driver)	Digital Incremental Encoder (2 channel with or without Line Driver)
	DC Tacho	DC Tacho
	Without sensor (DC motors)	Without sensor (DC motors)
	Digital Hall Sensors (EC motors)	Digital Hall Sensors (EC motors)
<b>Operating mode</b>		
	Current controller (torque control), Speed controller (closed and open loop)	Current controller (torque control), Speed controller (closed and open loop)
<b>Electrical data</b>		
Nominal operating voltage $V_{CC}$	10 - 50 VDC	10 - 50 VDC
Max. output voltage	$0.98 \times V_{CC}$	$0.98 \times V_{CC}$
Max. output current	15 A (<20 s)	15 A (<20 s)
Continuous output current	8 A	8 A
Pulse width modulation frequency	53.6 kHz	53.6 kHz
Sampling rate PI current controller	53.6 kHz	53.6 kHz
Sampling rate PI speed controller	5.36 kHz	5.36 kHz
Max. efficiency	99%	99%
Max. speed (DC)	limited by max. speed (motor) and max. output voltage (controller)	limited by max. speed (motor) and max. output voltage (controller)
Max. speed (EC; 1 pole pair)	150 000 rpm	150 000 rpm
Built-in motor choke	-	-
<b>Inputs/Outputs</b>		
Hall sensor signals	H1, H2, H3	H1, H2, H3
Encoder signals	A, A\, B, B\	A, A\, B, B\
Max. encoder input frequency differential (single-ended)	1 MHz (100 kHz)	1 MHz (100 kHz)
Potentiometers	-	-
Digital inputs	2	2
Digital inputs/outputs	2	2
Analog inputs	2	2
Resolution, Range, Circuit	12-bit, -10...+10 V, differential	12-bit, -10...+10 V, differential
Analog outputs	2	2
Resolution, Range, Max. output current	12-bit, -4...+4 V, 1 mA	12-bit, -4...+4 V, 1 mA
Auxiliary voltage output	+5 VDC (IL ≤10 mA)	+5 VDC (IL ≤10 mA)
Hall sensor supply voltage	+5 VDC (IL ≤30 mA)	+5 VDC (IL ≤30 mA)
Encoder supply voltage	+5 VDC (IL ≤70 mA)	+5 VDC (IL ≤70 mA)
Status Indicators	Operation: green LED / Error: red LED	Operation: green LED / Error: red LED
<b>Environmental conditions</b>		
Temperature - Operation	-40...+45°C	-40...+65°C
Temperature - Extended range	+45...+85°C; Derating: see device reference	+65...+92°C; Derating: see device reference
Temperature - Storage	-40...+85°C	-40...+85°C
Humidity (condensation not permitted)	5...90%	5...90%
<b>Mechanical data</b>		
Weight	Approx. 16 g	Approx. 84 g
Dimensions (L x W x H)	53.3 x 37.5 x 14.5 mm	53.3 x 37.5 x 30.6 mm
Mounting holes	Plugable (socket headers with 2.54 mm pitch)	Plugable (socket headers with 2.54 mm pitch)
<b>Part numbers</b>		
	<b>532872 ESCON Module 50/8</b>	<b>586137 ESCON Module 50/8 HE</b>
	Order accessories separately, from page 558	Order accessories separately, from page 558